



NEW

Four Colors in One Light.

Fireball® **FB2LED/FB2LEDX** is available
in Quad-Color LED models.



FEATURES

- Available in 12-24VDC or 120-240VAC
- Indoor/outdoor use
- Four LED color options (Amber, Blue, Green, and Red)
- Four light effects (60 FPM, 120 FPM, simulated strobe, and steady)
- 16 different color and flash combinations
- Integrated 1/2-inch NPT pipe and surface mount
- Conformal coated PCBA to protect against corrosion, vibration, water and dust ingress, and high-pressure and temperature spray-downs

SPECIFICATIONS

- 50,000-hour LED
- Operating Current
12-24VDC @ 0.32A-0.17A or 120-240VAC @ 0.055A
- Operating Temperature
-40°F to 150°F (-40°C to 66°C)

CERTIFICATIONS

- Type 4X, IP66 Enclosure
- IP69K compliant
- FB2LED-QC – UL and cUL Listed
- FB2LEDX-QC – UL and cUL Listed for Class 1, Division 2, Groups A, B, C, and D (T5); Class II, Division 2, Groups F and G (T6); Class III (T6)



HOW TO ORDER

Model	Description	UPC
FB2LED-QC-012-024	Fireball LED Warning Light, Quad Color, 12-24 VDC	782979252146
FB2LED-QC-120-240	Fireball LED Warning Light, Quad Color, 120-240 VAC	782979252153
FB2LEDX-QC-012-024	Fireball Hazardous Location LED Warning Light, Quad Color, wire guard, 12-24 VDC	782979252344
FB2LEDX-QC-120-240	Fireball Hazardous Location LED Warning Light, Quad Color, wire guard, 120-240 VAC	782979252351

PROGRAMMING

Works with standard PLC relay output cards or standard sourcing modules, and can be programmed and managed through PLC software

